

K624i

PROFESSIONAL CHOICE FOR LONG DISTANCES



PRODUCT HIGHLIGHTS



- Wide field of view, exceptionally comfortable eyepiece and high contrast image
- Precise, clearly defined click mechanism and reliable repeat accuracy
- Optional left or right side windage
- Parallax wheel integrated into the elevation turret (patented) (50 m to ∞)
- Precise illuminated reticles in 1 st focal plane

The K624i sets standards in handling and ergonomics thanks to the unique arrangement of its operating elements. It offers outstanding optical performance, mechanical perfection and a unique range of well proven reticles for professionals and competition shooters.

TECHNICAL DATA

Magnification:	6 - 24
Objective lens diameter:	56 mm
Exit pupil:	9.4-2.3 mm
Eye relief:	90 mm
Field of view:	6.8 - 1.7 m/100 m
Diopter compensation:	+2 / -3.5 dpt
Twilight factor (DIN 58388):	18.3 - 36.7
Impact correction per click:	0.1 MRAD $\frac{1}{4}$ MOA
Adjustment range (E/W):	25.5 / 11.25 MIL
Parallax adjustment:	50 m till ∞
Tube diameter:	34 mm
Length:	405 mm
Weight:	950 g
Focal plane:	1
Illuminated:	Ja

Warranty:

10 years

FEATURES



1st focal plane



Main tube 34 mm



Adjustment direction
CW or CCW



Windage left or right




Zero Stop




MIL


RETICLES / SUBTENSIONS




MSR/Ki



Mil3




Mil4




SKMR



SKMR3



AMR



MOAK